



FLEXIBLE POWERED CONVEYOR

Expedite product receiving, shipping and cross-docking with the new Cannon Equipment Flexible Powered Conveyor. This solution makes quick and simple work of moving product to and from the truck – even in tight loading areas – so you can bring down receiving costs and improve your operations.

- **Flexible.** Versatile design to quickly move product in large or small areas and even around tight corners
- **Operator Friendly.** Large locking durable casters and conveniently located operator touchpoints make it simple to move into place and stow when not in use
- **Smart and Secure.** Zero pressure accumulation technology controls each zone to prevent product from damage in transit



IMPROVED
COST SAVINGS



INCREASED
EFFICIENCY



SOLVING COMPLEXITY
WITH SIMPLICITY

Features

- Fully retractable for convenient storage when not in use
- Large casters allow easy movement of the conveyor and can be locked to keep the system safely in place
- Conveniently located controls make it simple to start/stop material flow as needed
- LED lighting on loading cart improves visibility in low light areas
- Color-coded drive belts make it simple to identify key areas of the drive system
- Heavy-duty powered loading cart helps keep conveyor operating smoothly
- 120 volt AC power does not require special power source
- Backed by a two-year warranty

HELPING YOU DO WHAT YOU DO, BETTER

Looking for this cart solution or something similar? Cannon Equipment designs and deploys custom material handling carts, equipment, conveyance, and aftermarket parts that help you improve operations, gain efficiencies, and reduce costs.

Specifications

- Length (extended):** 32'-176' (see chart below for details)
Length (collapsed): 14.5' – 71' (see chart below for details)
Roller Width: 28"
Height: Adjustable from 32"-38"
Speed: Adjustable up to 120 fpm; factory default is 70 fpm
Roller Diameter: 1.5", 1.9" on Heavy-Duty Loader Cart
Axle Center: 5" Standard, Adjustable from 3"-5"
Zero Pressure Accumulation: Bed-mounted sensor bar, 1 per zone, standard
Weight Capacity: 100 lbs. per linear foot on standard conveyor, 350lbs on Heavy-Duty Loading Cart
Power: 120V AC
Casters: 8" diameter, 360° rotating, non-marking, locking
Lights: LED lights standard

| Flexible Powered Conveyor Length (ft.) | | | | |
|--|--------------------------------|-------|-------|-------------------|
| # of Standard Sections | Extended Length by Axle Center | | | Compressed Length |
| | 3" | 4" | 5" | |
| HDLC Only | 32.3 | 26.9 | 21.5 | 14.5 |
| 1 | 61.1 | 50.4 | 39.7 | 25.8 |
| 2 | 89.9 | 73.9 | 57.9 | 37.1 |
| 3 | 118.7 | 97.4 | 76.1 | 48.4 |
| 4 | 147.5 | 120.9 | 94.3 | 59.7 |
| 5 | 176.3 | 144.4 | 112.5 | 71.0 |

Configuration includes one Heavy-Duty Loading Cart (HDLC).

cannon TM
E Q U I P M E N T

Contact Us Today:

-  cannonequipment.com
-  1.800.825.8501
-  info@cannonequipment.com
-  324 Washington Street W
Cannon Falls, MN 55009

